

CURRENT VERSION OF THE CLAIMS

The following listing of claims is the current version of the claims:

LISTING OF CLAIMS:

1. (Original): A polarizing element comprising a reflective polarizing plate for separating incident natural light into reflected light and transmitted light both of which are composed of polarized light, and a light-diffusion pressure-sensitive adhesive layer provided to the reflective polarizing plate.
2. (Previously presented): The polarizing element according to claim 1, wherein the reflective polarizing plate is a combination of a circularly-polarized light separation plate and a retardation plate.
3. (Original): The polarizing element according to claim 2, wherein the circularly-polarized light separation plate comprises a cholesteric liquid crystal layer.
4. (Previously presented): The polarizing element according to claim 3, wherein the cholesteric liquid crystal layer is a liquid crystal polymer layer that is Grandjean-oriented on a transparent polymer substrate via an orientation film.
5. (Previously presented): The polarizing element according to claim 4, wherein the cholesteric liquid crystal layer has a superimposed structure of cholesteric liquid crystal layers different from each other in a helical pitch of the Grandjean orientation.
6. (Original): The polarizing element according to claim 2, wherein the retardation plate is a quarter wavelength plate.
7. (Original): The polarizing element according to claim 2, wherein the light-diffusion pressure-sensitive adhesive layer is interposed between the circularly-polarized light separation

plate and the retardation plate.

8. (Original): The polarizing element according to claim 1, wherein the light-diffusion pressure-sensitive adhesive layer is made of a polymer containing uncolored transparent particles.

9. (Original): The polarizing element according to claim 8, wherein the polymer is an acrylic polymer having a weight average molecular weight of at least 100,000.

10. (Original): The polarizing element according to claim 8, wherein the uncolored transparent particles having an average particle diameter ranging from 0.5 μm to 20 μm are selected from inorganic particles and organic particles.

11. (Original): The polarizing element according to claim 1, wherein the light-diffusion pressure-sensitive adhesive layer is provided adjacent to the reflective polarizing plate.

12. (Original): A liquid crystal display having a polarizing element comprising a reflective polarizing plate for separating incident natural light into reflected light and transmitted light both of which are composed of polarized light, and also a light-diffusion pressure-sensitive adhesive layer provided to the reflective polarizing plate.

13. (Original): A method of manufacturing a polarizing element, wherein the polarizing element comprises a reflective polarizing plate for separating incident natural light into reflected light and transmitted light both of which are composed of polarized light, and a light-diffusion pressure-sensitive adhesive layer provided to the reflective polarizing plate.

14. (Original): The method according to claim 13, wherein the light-diffusion pressure-sensitive adhesive layer is provided adjacent to the reflective polarizing plate.

15. (Previously presented): The method according to claim 13, wherein the reflective polarizing plate is a combination of a circularly-polarized light separation plate and a retardation

plate.

16. (Original): The method according to claim 13, wherein the light-diffusion pressure-sensitive adhesive layer is made of a polymer containing uncolored transparent particles.

17. (Original): The method according to claim 16, wherein the polymer is an acrylic polymer having a weight average molecular weight of at least 100,000.

18. (Original): The method according to claim 16, wherein the uncolored transparent particles having an average particle diameter ranging from 0.5 μm to 20 μm are selected from inorganic particles and organic particles.

19. (Previously presented): The polarizing element according to claim 1, wherein the reflective polarizing plate is a linearly-polarized light separation plate.

20. (Previously presented): The polarizing element according to claim 1, wherein the reflective polarizing plate is a circularly-polarized light separation plate.

21. (Previously presented): The polarizing element according to claim 19, wherein the circularly-polarized light separation plate comprises a cholesteric liquid crystal layer.

22. (Previously presented): The polarizing element according to claim 20, wherein the cholesteric liquid crystal layer is a liquid crystal polymer layer that is Grandjean-oriented on a transparent polymer substrate via an orientation film.

23. (Previously presented): The polarizing element according to claim 21, wherein the cholesteric liquid crystal layer has a superimposed structure of cholesteric liquid crystal layers different from each other in a helical pitch of the Grandjean orientation.

24. (Previously presented): The method according to claim 13, wherein the reflective polarizing plate is a linearly-polarized light separation plate.

Serial Number: 10/072,455

Group Art Unit: 2871

25. (Previously presented): The method according to claim 13, wherein the reflective polarizing plate is a circularly-polarized light separation plate.